



presto Putty for metal "styrene-free" is a 2-component polyester metal putty with different eco-friendly fillers and aluminium pigments. Applicable as body filler in the field of car repair, engineering and hobby. Anywhere, where an extensive spread is desired. Subsurfaces like metal, wood, different plastics or concrete can be filled easily in the required number of coats. Holes will be filled and levelled, thin coats will be stabilised.

**Ord.-no:** 443466

#### Quality & properties

- Highly thixotropic, therefore very easy and pore-free white-spread working
- Easy processing
- Very good adherence
- Easy to sand
- High elasticity
- Free of asbestos and silicone
- Resistant to weak acids and bases, propellants, solvents, water and de-icing salt

#### Physical & chemical data

- Base: Polyester resin
- Colourname: grey
- Completely dry: 30 - 40 min
- Overcoatable: 30 - 40 min
- Surfaces: metal, various plastics, wood, concrete
- Minimum Working Temperature: 12 °C
- Maximum Working Temperature: 30 °C
- Flash point: 52
- Storage stability: 1.5 y
- Content: 250 G

#### How to use

The area to be repaired should be derusted, clean, dry, free of grease and sanded.  
Take the required amount of material from the can and mix it well with the corresponding quantity of hardener.  
Apply the mixed material in the desired layer thickness.  
After approx. 30-40 minutes the repaired spot can be drilled, sanded, sawed, rasped and painted.  
Clean tools immediately after use, if necessary with a nitro thinner.  
Do not return mixed material into the can.

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.