

presto Conservation Wax

Technical Information



presto Conservation Wax is a rust-protecting preservation wax for long-term protection of the engine interior, folds, surfaces and cavities on cars, two-wheelers and machines of all kinds. Leaves a firmly adhering, light protective film after drying.

Ord.-no: 157158

Quality & properties

- Transparent protective film
- Good corrosion protection
- Adheres to painted and untreated surfaces
- No dripping or running
- Simple application
- Excellent adhesion
- Resistant to effects of weather
- Resistant to weak acids and alkalines
- Silicone-free

Physical & chemical data

- Base: Special resin
- Colourname: white-transparent
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Temperature Resistance: 180 °C
- Storage stability: 10 y
- Content: 400 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Surface should be clean, dry and free of grease.
- Spray on a thin coat.
- A protective, transparent film remains once evaporated (the film can be removed with presto Engine Cleaner).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.