



presto Assembly Cleaner is a highly effective rapid cleaner for the maintenance, repair and installation of machinery, vehicles, precision mechanical and tools. It dissolves old and hardened oil and fat residues as well as remnants of brake fluid and silicone.

The cleaner serves as pre and basic cleaning and degreases all sliding surfaces and parts prior to the application of special lubricants.

Ord.-no: 157196

Quality & properties

- Removes tough oil and grease
- High solvency power
- Powerful directed jet spray
- Leaves no residue
- Non-conductive
- Can be sprayed from any angle due to a special 360° valve
- Non-corrosive
- Washable by strong water jet

Physical & chemical data

- Base: Special resin
- Colourname: transparent
- Surfaces: sliding surfaces and parts of vehicles, precision mechanical and tools.
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a. °C
- Storage stability: 10 y
- Content: 500 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Cover painted and plastic parts.
- Shake can before use.
- Spray the parts to be treated until the dirt disappears.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.