

presto Sealant Remover

Technical Information



presto Sealant Remover is suitable for the quick and easy removal of burnt-on and dried-on adhesive residues, sealing materials, oil carbon residues, paints, oils, greases etc. from engine and machine parts. Due to the high viscosity, the seal remover is highly efficient.

Ord.-no: 157080

Quality & properties

- High solvency power
- Light gel structure
- Maximum impact due to high level of viscosity
- Can also be applied effectively to vertical surfaces
- Special additives guarantee long-lasting deep action
- Highly effective solvent
- Non corrosive
- Non conductive
- Directed jet spray

Physical & chemical data

- Base: Methylal
- Colourname: yellowish-transparent
- Surfaces: engine and machine parts
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 400 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Cover coated or plastic parts.
- Spray the residue to be removed from a distance of ca. 25-30 cm and leave to work for 10 minutes.
- Carefully remove loosened residue with a spatula.
- Repeat process on stubborn dirt.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.