

## presto Cold Shock Spray

## Technical Information



presto Cold Shock Spray is a highly effective tool for loosening rusted or pressed connections e.g. Screws, nuts, bolts, crankshafts. Special ingredients create a short-term "cold shock" (-50 °C) on the rusted workpiece, which causes shrinkage.

**Ord.-no:** 211881, 100013

### Quality & properties

- Short-term cold shock -50°C
- Works in seconds
- Leaves no residue
- Free from fat and silicone
- To avoid damage by heat during soldering
- Directed jet spray
- Can be sprayed from any angle due to a special 360° valve

### Physical & chemical data

- Base: Special resin
- Colourname: brownly-transparent
- Surfaces: Screws, nuts, bolts, crankshafts.
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point:
  - n.a.
  - n.a. °C
- Storage stability: 10 y
- Content: 400 ML

### How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can vigorously before use.
- Spray the screws with several short sprays for several seconds.
- The fast temperature drop means screws can be loosened.
- Do not spray on skin or body parts!

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.