

presto PTFE-Spray dry

Technical Information



Dry surface lubricant for treating mechanical parts made of metal and plastic e.g. folding roofs, door locks, slideways, seat tracks, seat belts, windscreen wipers, zips and oven hinges.

Ord.-no: 279911, 429972

Quality & properties

- Leaves behind pure PTFE, no grease or oil (dry film)
- Very low friction coefficient
- Excellent adhesion
- Prevents wear and clamping
- Special valve allows application in any position (360° valve)
- Also suitable as an anti adhesive for injection moulds that are not allowed to come into contact with silicone (release spray)
- Suitable for parts that are exposed to light loads and/or low speeds
- Directed jet spray

Physical & chemical data

- Base: PTFE
- Colourname: white transparent
- Surfaces: mechanical parts made of metal and plastic
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content:
 - 400 ML
 - 150 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can vigorously before use.
- Apply presto PTFE Spray dry in a thin even layer.
- A dry PTFE film is left after evaporation (approx. 1 minute).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.