

presto Epoxy-Primer

Technical Information



presto Epoxy primer is an all-purpose 1K primer that provides excellent adhesion and corrosion prevention on sheet steel, zinc-coated steel, aluminium and anodised aluminium. It is fast drying with good flow and can be applied wet-on-wet. It also offers good insulation against humidity.

Ord.-no: 502637

Quality & properties

- Simple, time-saving application
- Recoatable with solvent and water based topcoats
- Fast drying and good flow
- Good insulation against moisture
- Wet-on-wet application possible

Physical & chemical data

- Base: 1K Epoxy resin
- Colourname: grey
- Degree of gloss: mat
- Efficiency: 400 ML – 1 m²
- Overcoatable: 30 - 40 min
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 400 ML

How to use

The surface should be derusted, clean, dry, free of grease (with preso Silicone Remover) and sanded. Shake can for at least 2 minutes from the audible noise of the ball agitators. Test spray at an invisible spot. Apply several thin layers at a distance of 15-20 cm. Spray to test.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.