



presto Oil Stain Remover is an effective cleaner for all absorbent and non-absorbent surfaces such as concrete, stone floors, clinker or ceramic. Particularly suited to workshop floors.

Ord.-no: 157172

Quality & properties

High solvency and absorption
Effective
Simple application due to overhead-application
Directed jet spray

Physical & chemical data

Base: Special resin
Colourname: white-transparent
Surfaces: stone floors, clinker or ceramic
Minimum Working Temperature: 5 °C
Maximum Working Temperature: 30 °C
Flash point: n.a.
Storage stability: 10 y
Content: 400 ML

How to use

Bring the can to room temperature.
Operating temperature 5° to 30°C.
Shake can vigorously before use.
Spray onto the surface to be treated in a vertical position and from a distance of ca. 5 cm and leave to work for ca. 10 minutes.
Oil is absorbed due to the special recipe, leaving a powdery residue.
Sweep up residue and dispose of in the correct manner.
Repeat process with stubborn dirt.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.