

presto Universal Spray

Technical Information



presto Universal Spray is a special product, based on acrylic resin and high quality pigments. For contrast and partial lacquering, for example rally stripes at the car and many other purposes. Also applicable on rims and car body.

Ord.-no: 428955, 385810, 428948, 428962, 385803, 501784, 100008

Quality & properties

- Fast drying
- High-grade quality
- Suitable for indoors and outdoors applications
- Very good coverage
- Excellent adhesion
- Scratch-, shock- and impact-resistant
- Weather-resistant, light-proof, UV-resistant
- High surface hardness and good elasticity
- Good flow, smooth surface
- Limited resistance against petrol

Physical & chemical data

- Base: Acrylic resin
- Colourname:
 - black
 - white
- Degree of gloss:
 - mat GU
 - satin mat GU
 - gloss GU
- Efficiency:
 - 500 ML – 1.6 m²
 - 500 ML – 9,6 m²
- Dry to touch: 50 min
- Dust dry: 10 min
- Completely dry: 24 h
- Overcoatable: 24 h
- Surfaces: wood, metal, aluminium, glas, stone, different plastics
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 500 ML

How to use

The surface must be clean, dry, rust and grease free.
Fill and sand uneven surfaces. If no filling with putty is necessary, apply presto Universal Primer
Shake can for 3 minutes before use.
Test spray at an invisible spot.
Spray distance approx. 20-30 cm.
Spray several thin cross-coats in 3 - 5 minute intervals.
Coat with presto Universal Clear Lacquer to protect the paint.
Do not spray over synthetic paints!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.