

presto PTFE-Spray

Technical Information



presto PTFE Spray (universal lubricant) is a high-quality synthetic all-purpose lubricant with powerful moisture and rust repellent properties. This high-performance lubricant dries leaving no residue.

Application areas:

- Car: door hinges, sunroof, locks, window guides, antennae, chains, electric wiring
- Mopeds, bicycles: gear chain, rims, pedal shafts
- Boats, caravans: wiring, sliding doors, tools

Ord.-no: 306338

Quality & properties

High creeping capability
 Very low friction coefficient
 Prevents wear and clamping on the treated parts
 Excellent mechanical and thermo stability
 Silicone free
 Very fine structure (particle size: ca. 5 micrometres)
 Excellent adhesion
 Resistant to the effects of weather
 Protects from corrosion
 Water-repellent

Physical & chemical data

Base: Mineral oil with PTFE
 Colourname: white transparent
 Surfaces: door hinges, sunroof, locks, window guides, antennae, chains, electric wiring, gear chain, rims, pedal shafts, wiring, sliding doors, tools
 Minimum Working Temperature: 5 °C
 Maximum Working Temperature: 30 °C
 Flash point: n.a.
 Storage stability: 10 y
 Content: 400 ML

How to use

Bring the can to room temperature.
 Operating temperature 5° to 30°C.
 Shake can for 2 minutes before use.
 Surface should be clean, dry and free of grease.
 Apply in fine even coats.
 Shake can from time to time during use.
 Optimum lubrication is achieved once the solvent has evaporated.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.