

presto Vaseline Spray

Technical Information



presto Vaseline Spray is a reliable lubrication that also protects metals such as aluminium, copper, brass, chrome, steel etc. from acids, lyres and salt.

Application areas:

Antennae, plug-in connections and bolted connections and locks

Ord.-no: 306376

Quality & properties

- Medicinal qualities
- Non-poisonous on contact with food
- Excellent lubrication
- Water repellent
- Insulating effect
- Prevents wear and clamping of treated parts
- Excellent mechanical stability
- Excellent adhesion
- Acid free
- Good corrosion protection

Physical & chemical data

- Base: Vaseline
- Colourname: white
- Surfaces: metal
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 400 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Surface should be clean, dry and free of grease.
- Spray onto the parts to be treated.
- Optimum lubrication occurs once the solvent has evaporated.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.