

presto Spray Grease white

Technical Information



presto White Grease is an adhesive lubricant for mechanical metal and plastic parts to prevent friction.

Application areas:

- Cars: door hinges, rolling and ball bearings, gear stick, throttle and clutch, hand brake parts, hinges, door locks, springs, sunroof
- Mopeds: ball bearings
- Boats, caravans: engine, hinges
- Free time: rollerblading

Ord.-no: 429798, 306352, 100012

Quality & properties

- High level of viscosity
- Good penetration
- Excellent corrosion and sliding protection
- Excellent adhesion
- Excellent mechanical and thermo stability
- Resistant to the effects of weather
- Water repellent
- Prevents the wear and clamping of treated parts
- Contains PTFE (Polytetrafluorethenes)
- Application scope between -30°C and +160°C

Physical & chemical data

- Base: EP-2 Grease with PTFE
- Colourname: beige
- Surfaces:
 - metal and plastic mechanical parts
 - mechanical metal and plastic parts
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point:
 - n.a.
 - n.a. °C
- Storage stability: 10 y
- Content:
 - 150 ML
 - 400 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Surface should be clean, dry and free of grease.
- Cover coated or plastic parts with masking tape.
- Spray generous amounts of white spray grease on the part to be lubricated, and then flash off for ca. 5 minutes.
- Shake can from time to time during use.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.