

presto Copper Paste

Technical Information



For universal use as an anti-seize paste (lubricant), assembly paste, screw paste, sealing agent. Separating agent and lubricant, corrosion protection grease, anti-squeak paste.

Ord.-no: 266874

Quality & properties

- Protects against welding, burning and seizing
- Prevents rusting and scaling
- Ensures uniform friction values and tightening torques for screws
- Very lubricating effect, high pressure absorption
- Seals well in corrosive environments
- Active and hot water resistant
- No coal formation at high temperatures

Physical & chemical data

- Colourname: copper-metallic
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 35 °C
- Flash point: 100 °C
- Storage stability: 2 y
- Content: 100 G

How to use

- Clean the surface to be treated.
- Apply presto copper paste evenly with a brush, rag, brush or sponge, excess is not harmful.
- Avoid mixing with third-party products.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.