

## presto Electro Protect

## Technical Information



Thanks to its extremely good creeping ability, presto electrical protection migrates into the smallest plug contacts and displaces water and moisture. Parts are protected against rust and dirt. Dissolves oxidised contacts.

Application areas:

Switches, cables, plugs, spark plugs, fuses

Ord.-no: 306369

### Quality & properties

- Liquid isolation agent
- Good penetration effect
- Water repellent
- Loosens oxidised contact points
- Corrosion protection effect
- Extremely good penetration
- Fast acting
- Prevent ignition problems
- Water, salt and weak acids and alkaline proof
- Can be sprayed from any angle due to a special 360°C valve

### Physical & chemical data

- Base: Mineral oil
- Colourname: transparent
- Surfaces: engine parts
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 400 ML

### How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Surface should be clean, dry and free of grease.
- Switch off electronic equipment before use.
- Apply electro protect spray in thin layers.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.