

presto Cold Shock Rust Solvent

Technical Information



presto Cold Shock Rust Solvent is a highly effective tool for loosening rusted components by generating local cooling e. g. for screws, nuts, bolts, crankshafts. Special ingredients create a short-term "cold shock" (-30 ° C) on the rusted workpiece, which causes shrinkage and at the same time allows the lubricating components to penetrate.

Ord.-no: 157233, 429927

Quality & properties

- Contains highly-effective penetration and lubrication substances (mineral-based)
- Short-term cold shock -30°C
- Works in seconds
- Leaves no residue
- Directed jet spray
- Simple application

Physical & chemical data

- Base: Special resin
- Colourname: brown-transparent
- Surfaces: Screws, nuts, bolts, crankshafts.
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content:
 - 400 ML
 - 150 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can vigorously before use.
- Spray the screws with several short sprays for several seconds.
- The fast temperature drop in combination with the lubrication means screws can be loosened.
- Do not spray on skin or body parts!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.