

presto Leak Detector Spray

Technical Information



Leaks in compressed air and gas flow systems can be detected by using the high-quality presto Leak Detector Spray. Bubble will indicate where the leak is. The foam is easy to wash off with water. It leaves no residue that could impede repair work. DVGW certificate no. NG/5170BR0105.

Application areas:

Pipes, hoses, tyres, tanks, compressors, pressure switch, compressed air bottles, refrigerant circuits and systems with combustible gases.

Ord.-no: 157219

Quality & properties

- Good spreading rate
- DVGW-certified
- Solvent free
- Slightly alkaline and foam forming
- Works up to outdoor temperatures of 0°C
- Non-combustible
- Non-corrosive
- Surplus spray can easily be washed off with water
- Contains rust-protective inhibitors

Physical & chemical data

- Base: Tenside solution
- Colourname: transparent
- Surfaces: Pipelines, tubes, tires, tanks, compressors, pressure switches, compressed air cylinders, refrigerant circuits and systems with combustible gases
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: 100 °C
- Storage stability: 10 y
- Content: 300 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Spray the object that needs to be examined from the usual distance until a sealed film has formed.
- Bubbles will indicate the leaks.
- Finally, surplus foam can be washed off with water.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.