

presto Rust Solvent

Technical Information



presto Rust Solvent reduces friction and enables tight bolts or rusted parts to be unscrewed easily. The product is fast working, efficient and flows and works its way around objects such as screws – even going against gravity. Enriched with molybdenum sulphide, it offers improved lubricating properties. presto Rust Solvent does not damage metal, rubber and numerous plastics.

Application areas:

Hinges, fittings, bolted connections, locks, bolts, nuts, tools, chain etc.

Ord.-no: 306314, 429781

Quality & properties

- High penetrability
- Good penetration
- Contains MOS2 and graphite
- Long-lasting lubricating effect
- Non-corrosive

Physical & chemical data

- Base: Special resin
- Colourname: graphite/black
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: 0 °C
- Storage stability: 10 y
- Content:
 - 400 ML
 - 150 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Remove loose rust with a wire brush.
- Spray parts and leave to take effect.
- Starts working in most cases within 5 to 15 minutes, depending on the ability of the product to penetrate.
- Dirt and rust can already be removed from stuck parts after 5 minutes.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.