

presto Wheel Protection Wax

Technical Information



Protects rims and hubcaps by forming an invisible wax coating from rapid soiling. Gives a glossy result and reduces the adhesion of dirt.

Ord.-no: 383465

Quality & properties

- Reduces the adhesion of dirt
- Prevents aging
- Gives a glossy result
- User-friendly
- Free from solvents
- pH-neutral
- Contains silicone

Physical & chemical data

- Base: Special resin
- Colourname: milky white
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Storage stability: 5 y
- Content: 500 ML

How to use

- Shake before use.
- The surface should be clean and dry.
- Thorough cleaning with presto Wheel Cleaner recommended in advance.
- Apply presto Wheel Protection Wax in a thin, equal layer and polish with a soft cloth.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.