



Zinc-Alu-Spray for zinc-plated parts and surfaces, which have been damaged by welding, sanding, drilling, transportation etc., and which have to be repaired or adapted to colour shade.

Also suitable as excellent corrosion protection for metal surfaces and black iron metals. Suitable for only a limited extent on aluminium.

Ord.-no: 795664

Quality & properties

Rust-protecting
Heat-resistant up to 300°C
Good flow
Coatable with air-drying acrylic, nitro-combi and synthetic lacquers
Resistant to changing temperatures

Physical & chemical data

Base: Special resin
Colourname: silver-metallic
Degree of gloss: satin mat GU
Efficiency: 400 ML – 1.5 m²
Dry to touch: 60 min
Dust dry: 15 min
Completely dry: 12 h
Surfaces: zinc-plated parts, metal surfaces, black iron metals
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 30 °C
Flash point: n.a.
Storage stability: 10 y
Content: 400 ML

How to use

The surface must be clean, dry, rust and grease free.
Shake can for 2 minutes before use.
Test spray at an invisible spot.
Apply several covering coats.
Spray distance approx. 25 cm.
After drying (approx. 24 hours) primer and top coat can be applied.
It is not recommended to overpaint with other lacquers.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed of as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.