

presto Battery-Pole-Protection

Technical Information



presto Battery Pole Protection Spray protects electrical contacts and battery terminals from oxidation and corrosion. The blue wax ensures a constant flow of electricity and prevents leakage and voltage losses. It extends the life of a battery and prevents acid damage. Good compatibility with plastics.
Applications: battery terminals, battery holders, terminals, earth cables

Ord.-no: 157059, 429989

Quality & properties

- Long-term prevention from corrosion and oxidation
- Extends the life of a battery
- Reduces leakage currents
- Safe ignition and bright lighting
- Insulating effect
- Reduces contact resistance
- Prevents acid damage

Physical & chemical data

- Base: Special resin
- Colourname: blue
- Surfaces: electrical contacts and battery terminals
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content:
 - 400 ML
 - 150 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can vigorously before use.
- Parts to be protected must be clean and dry.
- Spray a thin layer of battery terminal protection on the parts to be treated.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.