

## presto Contact Spray

Ord.-no.: 157141, 429910

### Technical Information



Contact resistances, leakage currents and voltage losses in electrical connections are reliably eliminated with presto Contact Spray. The smooth flow of electricity is guaranteed. Application areas: Electrical connections, radios, televisions, tools, wiring, connections

#### Quality & properties

- Water and moisture are infiltrated and displaced
- Protects contacts and prevents corrosion
- Excellent adhesion and penetration
- Resistant to water, salts and weak bases
- pH-neutral
- Directed jet spray

#### Physical & chemical data

- Base: Special resin
- Colourname: yellowish-transparent
- Surfaces: electrical connection
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Vapour pressure: 3500/20 bar
- Storage stability: 10 y
- Content:
  - ◊ 400 ML
  - ◊ 150 ML

#### How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can before use.
- Switch electrical equipment off before treating.
- Surface should be clean, dry and free of grease.
- Spray several thin layers on connectors, cables, distributor caps, etc.

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

**As of August 18, 2022** – This release replaces all eventually earlier issued versions.