



presto V-Belt Spray

Ord.-no.: 157042

Technical Information



presto V-Belt Spray stops and prevents slipping and squeaking V belts. Excellent adhesion ensures long-lasting protection as well as slowing down the wear and tear process.

Quality & properties

- Wear and tear protection
- Makes V belts smoother and lengthen lifespan
- Excellent adhesion
- Improves traction
- Resistant to the effects of weather
- Directed jet spray
- Dilatant

Physical & chemical data

- Base: Polyalphaolefine
- Colourname: transparent
- Smell: Characteristic
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Spray rate: 1.15
- Vapour pressure: 3500/20 bar
- Relative density: 0.89 g/ml
- Storage stability: 10 y
- Content: 400 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Switch off engine.
- Apply a thin, even coat of V belt spray on the running surface of the V belt and leave to work
- Once the solvent has evaporated, the engine can be restarted.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.