

presto Anti-Welding Spray

Ord.-no.: 211898

Technical Information



presto Anti-Welding Spray prevents welding spatter from sticking to the welding nozzle and in the vicinity of the welding zone.

Quality & properties

- High spreading rate
- Non combustible
- Silicone free
- Leaves no residue
- Slightly alkaline, surplus spray can be removed with water and can be coated afterwards
- Non-corrosive
- Misty spray
- 360° valve allows application from every position

Physical & chemical data

- Base: Emulsifying oil
- Colourname: white-transparent
- Surfaces: welding nozzle, welding zone
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Spray rate: 2.7
- Vapour pressure: 8500/20 bar
- Flash point: >100 °C
- Relative density: 1 g/ml
- Storage stability: 10 y
- Content: 300 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Spray parts in need of protection and carry out welding work.
- Remove welding splatter with a steel brush.
- Remove surplus spray with water or a damp cloth.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.